

ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of:

Inventor: David R. Irvin and Ali S. Khayrallah

For: METHOD OF GENERATING CONTROL SIGNALS BASED ON LOCATION OF RADIO TERMINALS

Enclosed are:

- ☒ 8 sheets of drawing.
- ☐ An assignment of the invention to _____ application.
- ☐ A certified copy of a _____ application.
- ☐ An associate power of attorney.
- ☐ A verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27.
- ☐

The filing fee has been calculated as shown below:

	(Col. 1)	(Col. 2)
FOR:	NO. FILED	NO. EXTRA
BASIC FEE		
TOTAL CLAIMS	30 - 20 =	* 10
INDEP. CLAIMS	6 - 3 =	* 3
MULTIPLE DEPENDENT CLAIM PRESENTED		

*If the difference in Col. 1 is less than zero, enter 0 in Col. 2.

SMALL ENTITY	
RATE	FEE
	\$ 380
x 9 =	
x 39 =	
+ 130 =	
TOTAL	

OTHER THAN A SMALL ENTITY	
RATE	FEE
	\$ 760
x 18 =	\$180
x 78 =	\$234
+ 260 =	
TOTAL	\$1174

- ☐ Please charge my Deposit Account No. _____ the amount of \$ _____. A duplicate copy of this sheet is enclosed.
- ☒ A check in the amount of \$ 1,174.00 to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 23-0785. A duplicate copy of this sheet is enclosed.
- ☒ Any additional filing fees required under 37 CFR 1.16.
- ☒ Any patent application processing fees under 37 CFR 1.17.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 23-0785. A duplicate copy of this sheet is enclosed.
- ☒ Any patent application processing fees under 37 CFR 1.17.
- ☐ The issue fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).
- ☒ Any filing fees under 37 CFR 1.16 for presentation of extra claims.

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

"Express Mail" mailing label number EM114096704US
Date of Deposit April 8, 1999

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Karen A. Sanderson

(Typed or printed name of person mailing paper or fee)

Karen A. Sanderson
(Signature of person mailing paper or fee)

Respectfully submitted,

John S. Mortimer
John S. Mortimer, Reg. No. 30,407

-1-

METHOD OF GENERATING CONTROL SIGNALS BASED ON LOCATION OF RADIO TERMINALS

FIELD OF THE INVENTION

5 The present invention is generally directed toward wireless communications systems and, more particularly, toward the generation of a control signal when two or more radio terminals are at specified locations.

BACKGROUND OF THE INVENTION

10 U.S. Patent No. 5,638,423 teaches activating a wireless radio terminal, such as a cellular phone, in response to a signal received from a proximity user card over a short-range RF (Radio Frequency) link. The wireless terminal is activated for use when the wireless terminal and the proximity user card are within a predetermined distance from one another, which aids in preventing unauthorized use of the wireless terminal. The predetermined distance is set by the transceiving range between the proximity user card and the wireless terminal. However, a disadvantage of the method taught by U.S. Patent No. 5,638,423 is that it depends on signal amplitude of a low power, short-range RF link between the wireless terminal and the proximity user card, which is inherently unreliable.

15
20 The wireless terminal transmits an inquiry signal, via the low power, short-range RF link, to the card. If the wireless terminal's inquiry to the card goes unanswered, logic in the wireless terminal determines that the wireless terminal and the card are separated by a distance greater than the predetermined distance, and the wireless terminal transmits an invalid

-2-

proximity message and is kept locked. Since the range and reliability of a low power, short-range RF link varies according to signal loss imposed by its environment, the method of activating a wireless terminal for use as taught in U.S. Patent No. 5,638,423 is subject to erroneous determinations.

The disclosed method overcomes one or more of the above-mentioned problems.

SUMMARY OF THE INVENTION

A control signal is generated based on the location of one or more mobile radio terminals as determined, for example, by a global positioning system or, where the radio terminal is a cellular terminal, by cellular positioning. The method generally includes the steps of determining the location of a first mobile radio terminal, determining the location of a second mobile radio terminal, comparing the locations of the terminals, and generating a control signal based upon the comparison. The control signal may be generated if the first and second mobile radio terminals are within a specified distance of one another. Alternatively, the control signal may be generated if the first and second mobile radio terminals are separated by at least a specified distance from one another. Additionally, the control signal may be generated if it is determined that the first mobile radio terminal is at a first specified location and the second mobile radio terminal is at a second specified location spatially separated from the first specified location. Still further, the control signal may be generated if it is deter-

-3-

mined that the first and second mobile radio terminals are at the first and second specified locations at some particular time (or times).

In one form, the first mobile radio terminal is a mobile communication device and the second mobile radio terminal is a key permitting operation of the mobile communication device only when the key is within a predetermined distance from the mobile communication device. If the key is determined to be within the predetermined distance of the mobile communication device, the control signal activates the mobile communication device for use.

An alternative embodiment of the method includes the steps of determining locations of N mobile radio terminals (where $N \geq 2$), comparing the locations of the N mobile radio terminals with M different specified locations, wherein $M \leq N$, and generating a control signal if at least one of the N mobile radio terminals is determined to be located at each of the M different specified locations, or if each of the N terminals is at its assigned specified location.

In one form of the alternative embodiment, the step of determining locations of the N mobile radio terminals includes the step of continuously monitoring, via a central server remote from the N mobile radio terminals, the locations of the N mobile radio terminals.

A further embodiment of the method includes the steps of receiving, at a location server, an initiation signal from a first mobile radio terminal, and transmitting, by the location server, a location query to the first and second mobile radio terminals. In response to the location query,

-4-

the first and second mobile radio terminals report their respective locations to the location server. The location server compares the received locations of the first and second mobile radio terminals and generates a control signal based upon the comparison.

5 In one form of the further embodiment, the initiation signal from the first mobile radio terminal includes the location of the first mobile radio terminal, wherein the location server need only transmit a location query to the second mobile radio terminal.

Location information of the first and second mobile radio terminals, or of the N mobile radio terminals, may be provided by a GPS receiver in the mobile radio terminals or, for a cellular terminal, by cellular positioning.

10 It is an object of the disclosed method to generate a control signal when two or more mobile radio terminals are simultaneously in two or more prearranged positions. The positions may be relative to each other or absolute, and the control signal may be utilized to enable or inhibit a wide variety of applications.

15 Other aspects, objects and advantages of the disclosed method can be obtained from a study of the application, the drawings, and the appended claims.

20 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of a cellular phone used in the generation of a control signal based on location;

Fig. 2 is a block diagram of a smart card used in the generation of a control signal based on location;

Fig. 3 is a flow chart illustrating the generation of a control signal based on the location of a cellular phone and a smart card;

5 Fig. 4 is a block diagram of a wireless communications system used in the generation of a control signal based on location;

Fig. 5 is a flow chart illustrating the generation of a control signal based on the location of first and second mobile radio terminals;

10 Fig. 6 is a flow chart illustrating an alternative form of generating a control signal based on the location of first and second mobile radio terminals;

Fig. 7 is a flow chart illustrating a further form of generating a control signal based on the location of first and second mobile radio terminals;

15 Fig. 8 is a block diagram of an alternative form of the wireless communications system shown in Fig. 4;

Fig. 9 is a block diagram of a wireless communications system used in the generation of a control signal based on the location of N mobile radio terminals; and

20 Fig. 10 is a block diagram of an alternative wireless communications system used in the generation of a control signal based on the location of N mobile radio terminals.

DETAILED DESCRIPTION OF THE INVENTION

A control signal is generated when two or more mobile radio terminals are simultaneously in two or more specified locations, and alternatively, when two or more mobile radio terminals are simultaneously in two or more specified locations at some particular time (or times). The control signal may be used to enable or inhibit a wide variety of applications. In one form, each of the wireless terminals is provided with a GPS (Global Positioning System) receiver for determining the location of the terminal. The control signal may be generated by any of the radio terminals, or by a location server remote from the radio terminals and in wireless communication therewith.

In one application, a cellular phone may be paired with a smart card carried by the user of the cellular phone. The cellular phone operates only when it is within a selected specified distance from the smart card. Thus, the smart card serves as a key for activating/unlocking the cellular phone.

Fig. 1 is a block diagram of a cellular phone, shown generally at 10, which includes a user interface 12 having visual display 14, keypad 16 and ringer 18 features, an audio I/O circuit 20 connected to a microphone 22 and a speaker 24, a microprocessor logic circuit 26 having a memory 28, a wide-range RF transceiver 30, a GPS receiver 32 and a short-range RF transceiver 34 all communicating, and receiving power from battery 36, via a system bus 38.

Fig. 2 is a block diagram of a smart card, shown generally at 40, which includes a microprocessor logic circuit 42 having a memory 44,

-7-

a short-range RF transceiver 46, a GPS receiver 48, and optionally a wide-range RF transceiver 50 all communicating, and receiving power from battery 52, via a system bus 54.

The GPS receivers 32 and 48 in the phone 10 and smart card 40 preferably turn on intermittently to detect the location of the respective terminal. The location of the phone 10 is stored in its memory 28, and similarly, the location of the smart card 40 is stored in its memory 44.

Operation when a user desires to activate the phone 10 for use will now be described with respect to Figs. 1-2 and the flow chart of Fig. 3. It should be understood that while operation will be described with specific reference to the phone 10 and smart card 40, the phone 10 and smart card 40 may be any wireless radio terminals.

Upon call activity, either incoming or outgoing, at the phone 10 at block 54, the microprocessor logic circuit 26 in the phone 10 queries the phone's 10 location at block 56. The microprocessor logic circuit 26, at block 56, may retrieve the last stored location of the phone 10 from the memory 28, or may activate the GPS receiver 32 to do a location check. The phone's microprocessor logic circuit 26 then queries the card's 40 location at block 58. Similarly, the card 40 may respond with the last location stored in its memory 44, or may activate its GPS receiver 48 to do a location check and respond with the determined location. The query from the phone 10, at block 58, and response from the card 40 are transmitted over a short-range RF link, for example, Bluetooth as described in "Bluetooth - The universal radio interface for *ad hoc*, wireless connectiv-

-8-

ity", Ericsson Review No. 3, 1998, established by short-range RF transceivers 34 and 46 in the phone 10 and card 40, respectively.

5 If a timely response is received from the card 40 at block 60, the microprocessor logic circuit 26 in the phone 10 compares the locations of the phone 10 and card 40 at block 62. If it is determined that the locations are within a specified range at block 64, the microprocessor logic circuit 26 in the phone 10 generates a control signal at block 66, to activate the phone 10 and allow the call to be processed. If the locations are not within a specified range or distance at block 64, the microprocessor logic circuit 26 in the phone 10 keeps the phone 10 locked or deactivated at block 68. If a timely response is not received from the card 40 at block 60, the microprocessor logic circuit 26 in the phone 10 keeps the phone 10 locked or deactivated at block 70. It should be understood that the decision to lock or unlock the phone 10 may also be made in the smart card 40. In this variation, the smart card 40 would send an authorization sequence to the phone 10, at block 66, over the short-range RF link to unlock or activate the phone 10.

10
15
20 In an alternative form, as shown in dotted lines in Fig. 3, after the positions of the phone 10 and card 40 are determined to be within a specified range at block 64, the current time, generally kept by a clock (not shown) internal to either the phone 10 and card 40 is compared with a preselect time, at block 71. The preselect time, set by a user, may be a particular point in time or a time range, *e.g.*, 1:00 PM - 4:00 PM. If the current time matches the preselect time at block 71, the control signal is
25 generated at block 66 to activate the phone 10 and allow the call to be

-9-

processed. If the current time does not match the preselect time, the phone 10 is kept locked or deactivated at block 68. By adding the time constraint, a user, such as a parent, is able to restrict use of the phone 10, such as by their children to whom the phone 10 may be given, to certain times of the day.

The determination of whether the phone 10 and card 40 are within a specified range may be made by a location server 72 remote from the phone 10 and card 40, as shown in Fig. 4. The location server 72 communicates with the phone 10 and card 40 via base station 74 and network 76, or may be physically located at the base station 74. The network 76 may be any type of network permitting voice or data communication between the base station 74 and location server 72, such as, but not limited to, a PSTN (Public Switching Telephone Network), the Internet, *etc.* Communication between the phone 10/card 40 and the base station 74 occurs over the wide-range RF link established by the RF transceivers 30 and 50 in the phone 10 and card 40, respectively, and an RF transceiver (not shown) in the base station 74. To support such wide-range communications, the phone 10 and card 40 each have a Mobile Identification Number (MIN) or Short-Message-Service (SMS) capability.

In operation, as shown in Figs. 1-2, 4 and the flow chart of Fig. 5, the phone 10 (1st terminal) transmits an initiation signal, such as an activation request signal or call set up signal, to the location server 72 via the base station 74 and network 76 at block 78. For convenience, communication will generally be described as taking place between the phone 10/card 40 and the location server 72, however, it should be understood

-10-

that all such communications occur via the base station 74 and network 76 (if the location server 72 is not at the base station 74). The initiation signal transmitted by the phone 10 at block 78, also includes data representing the location of the phone 10, which may be obtained by utilizing the last location stored in the phone's memory 28 or activating the phone's GPS receiver 32 to do a location check. Upon receipt of the initiation signal from the phone 10, the location server 72 transmits a location query to the card 40 (2nd terminal) at block 80. The card 40 receives the location query and transmits its location back to the location server 72 at block 82. The location of the card 40 may be obtained by either retrieving the last stored location of the card 40 from its memory 44 or activating the card's GPS receiver 48 to do a location check upon receipt of the location query from the location server 72. The location server 72 compares the received locations of the phone 10 and card 40 at block 84. If the server 72 determines that the locations of the phone 10 and card 40 are within a specified range, at block 86, the location server 72 generates a control signal at block 88, typically to activate the phone 10 allowing it to process the call. If the location server 72 determines that the locations of the phone 10 and card 40 are not within a specified range at block 86, the location server 72 does not generate a control signal, at block 90, keeping the phone 10 locked/deactivated.

In an alternative form, as shown in dotted lines in Fig. 5, after the locations of the phone 10 and card 40 are determined to be within a specified range at block 86, the location server 72 determines whether the current time, generally kept by a clock (not shown) internal to the location

-11-

server 72, matches a preselect time at block 91. The preselect time, set by a user of the system, may be a particular point in time or a time range, *e.g.*, 1:00 PM - 7:00 PM. If the current time matches the preselect time at block 91, the location server 72 generates a control signal at block 88. Otherwise, the location server 72 does not generate a control signal, at block 90.

In an alternative embodiment, as shown in Fig. 6, blocks 86, 88 and 90 have been replaced with blocks 86', 88' and 90'. The steps provided in blocks 78, 80, 82 and 84, and alternatively block 91, are performed in the same manner as previously described with respect to Fig. 5. After comparing the locations of the phone 10 and card 40 at block 84, the location server 72 determines whether the locations of the phone 10 and card 40 are separated by a predetermined distance at block 86'. If the location server 72 determines that the locations of the phone 10 and card 40 are separated by at least the specified distance at block 86', the location server 72 generates a control signal at block 88'. If, however, the locations of the phone 10 and card 40 are not separated by the specified distance, no control signal is generated by the location server 72 at block 90'.

Alternatively, generation of the control signal may occur according to the routine illustrated in Fig. 7. After initiation at block 92 by either the phone 10 or card 40, the location server 72 queries, at block 94, and receives, at block 96, the locations of the phone 10 (1st terminal) and card 40 (2nd terminal). The location server 72 then determines, at block 98, whether the phone 10 is at a first specified location. If not, the loca-

-12-

tion server 72 does not generate a control signal, at block 100, and exits the routine. If the phone 10 is at the first specified location, the location server 72 then determines whether the card 40 is at a second specified location at block 102. If not, the location server 72 does not generate a control signal, at block 104, and exits the routine. If the card 40 is determined to be at the second specified location, the location server 72 generates a control signal at block 106 and exits the routine. As previously noted, the control signal may be used to enable or inhibit a variety of applications.

In a further form, as shown in dotted lines in Fig. 7, after the location of the card 40 is determined to be at the second specified location at block 102, the location server 72 determines whether the current time, generally kept by a clock (not shown) internal to the location server 72, matches a preselect time at block 107. If the current time matches the preselect time at block 107, the location server generates a control signal at block 106 and exits the routine. Otherwise, the location server 72 does not generate a control signal, at block 110, and exits the routine.

Instead of the location server 72 requesting location information from each of the phone 10 and card 40, location information may be supplied to the location server 72 by a cellular positioning system 108, which monitors the location of each of the radio terminals (phone 10 and card 40), as shown in Fig. 8, thus alleviating the need for GPS receivers 32 and 48 in the phone 10 and card 40, respectively. This requires, however, that each of the mobile terminals be actively transmitting signals via their RF transceivers so that their location may be monitored by the cellular

-13-

positioning system 108. The phone signal utilized by the cellular positioning system 108 may be a communication signal or a registration signal intermittently transmitted by the cell phone 10/card 40. The determined location may be stored in a memory (not shown) resident within the cellular positioning system 108.

In each of the above-described methods utilizing the location server 72, the steps would essentially be the same except that the location server 72 would query the cellular positioning system 108 for the location of the respective radio terminals (phone 10 and card 40). Upon receipt of a location query from the location server 72, the cellular positioning system 108 may use the stored location of the respective radio terminal, if applicable, or may request that the radio terminal transmit a registration signal from which the cellular positioning system 108 may determine its location. Accordingly, a detailed discussion of each method utilizing the cellular positioning system 108 is not necessary.

While the control signal has been described as being generated by the location server 72, it should be understood that either the location server 72 or any of the radio terminals may generate the control signal. Upon determining that the criteria for the generation of the control signal have been met, the location server 72 would transmit an authorization sequence to the respective radio terminal initiating the generation of the control signal by the respective radio terminal.

The location server 72 may monitor, via base station 74 and network 76 (if the location server 72 is not at the base station 74), the location of a plurality of mobile radio terminals A-N, as shown in Fig. 9.

-14-

The location server 72 determines if the N different mobile radio terminals, where $N \geq 2$, are at M different locations, where $M \leq N$. The location server 72 determines whether terminals are at the M different locations, and generates an appropriate control signal. Alternatively, the location server 72 may generate the control signal when the N mobile terminals are not at the M different locations.

For example, a secure building may have M guard points. Each of N guards carries a radio terminal which generates a location signal monitored by the location server 72. The location server 72 generates a control signal automatically sealing the building when no guard is at one or more stations, and unlocking the building when all guards are present at their stations.

As shown in Fig. 10, the mobile radio terminals A-N may communicate directly with the location server 72 if the location server 72 includes a transceiver and is positioned within a sufficient operating range to receive the signals generated by the wireless mobile terminals A-N. In this embodiment, a short-range RF link may be established between the mobile radio terminals A-N and the location server 72. In the above example, this may be the case if the location server 72 was centrally located within the building.

In other applications utilizing the above-described methods, the operation of a marine or maritime phone may be tied to a particular boat having a built-in smart card; the operation of an emergency transceiver may be limited to the area surrounding a police car; the operation of a police car

-15-

or delivery vehicle may be disabled when an officer or delivery person carries a transceiver away from the car or vehicle; *etc.* In each application, the mobile radio terminals may exchange position information with each other via a short-range RF link, *e.g.*, Bluetooth, or by each having a Mobile Identification Number (MIN), or Short-Message-Service (SMS) capabilities and access to a location server, or directly to each other, via a wide-range RF link.

While the present invention has been described with particular reference to the drawings, it should be understood that various modifications could be made without departing from the spirit and scope of the present invention.

-16-

CLAIMS

1. A method of generating a control signal comprising the
2 steps of:

3 determining the location of a first mobile radio terminal;
4 determining the location of a second mobile radio terminal;
5 comparing the locations of the terminals; and
6 generating a control signal based upon said comparison.

7 2. The method of claim 1, wherein the step of generating a
8 control signal based upon said comparison comprises the step of generating
9 a control signal if the locations of the first and second mobile radio termi-
0 nals are within a specified distance of one another.

1 3. The method of claim 1, wherein the step of generating a
2 control signal based upon said comparison comprises the step of generating
3 a control signal if the locations of the first and second mobile radio termi-
4 nals are separated by at least a specified distance.

-17-

4. The method of claim 1, wherein the first mobile radio
terminal comprises a mobile communication device and the second mobile
radio terminal comprises a key permitting operation of the mobile communi-
cation device only when the key is within a specified distance from the
mobile communication device, and wherein the step of generating a control
signal based upon said comparison comprises the step of generating a
mobile communication device activation signal if the locations of the mobile
communication device and the key are within the specified distance.

5. The method of claim 1, wherein the step of generating a
control signal based upon said comparison comprises the step of generating
a control signal if the first mobile radio terminal is at a first specified loca-
tion and the second mobile radio terminal is at a second specified location.

6. The method of claim 5, wherein the first specified location
is spatially separated from the second specified location.

7. The method of claim 1, wherein the first and second mo-
bile radio terminals operate in a wireless communications system including
a base station and a location server communicating therewith, and wherein
the comparing and generating steps are performed at the location server.

8. The method of claim 1, wherein the comparing and gener-
ating steps are performed at one of the first and second mobile radio termi-
nals.

-18-

4 9. The method of claim 1, wherein the locations of the first
and second mobile radio terminals are determined by either a global or a
6 cellular positioning system, or a combination thereof.

2 10. The method of claim 1, wherein the comparing step
further comprises the step of comparing a current time with a preselect
time.

2 11. The method of claim 10, wherein the generating step
comprises the step of generating a control signal if the first mobile radio
terminal is at a first specified location, the second radio terminal is at a
4 second specified location and the current time matches the preselect time.

2 12. A method of generating a control signal comprising the
steps of:

 determining locations of N mobile radio terminals, wherein

4 $N \geq 2$;

6 comparing the locations of the N mobile terminals with M
different specified locations, wherein $M \leq N$; and

8 generating, in response to said comparison, a control signal if
at least one of the N mobile radio terminals is located at each of the M
different specified locations.

-19-

13. The method of claim 12, wherein the step of determining
locations of N mobile radio terminals comprises the step of continuously
monitoring, via a location server, the locations of the N mobile radio terminals.

14. The method of claim 12, wherein the N mobile radio
terminals operate in a wireless communications system including a base
station and a location server communicating therewith, and wherein the
comparing and generating steps are performed at the location server.

15. A method of generating a control signal comprising the
steps of:

determining locations of N mobile radio terminals, wherein
 $N \geq 2$;

comparing the locations of the N mobile radio terminals with
N specified locations assigned to each of the N mobile radio terminals; and
generating, in response to said comparison, a control signal if
each of the N mobile radio terminals is located at its assigned location.

16. The method of claim 15, wherein the N specified locations include N different specified locations.

-20-

17. A method of generating a control signal comprising the
4 steps of:

receiving, at a location server, an initiation signal from a first
6 mobile radio terminal, said initiation signal including the location of the first
mobile radio terminal;

8 transmitting, by the location server, a location query to a
second mobile radio terminal;

10 reporting, by the second mobile radio terminal, the location of
the second mobile radio terminal in response to the location query;

12 comparing, at the location server, the locations of the first and
second mobile radio terminals; and

14 generating a control signal based upon said comparison.

18. The method of claim 17, wherein the step of generating
a control signal based upon said comparison comprises the step of trans-
mitting, by the location server, a control signal activating the first mobile
4 radio terminal for use if the locations of the first and second mobile radio
terminals are either within, or separated by, a specified distance.

19. The method of claim 18, wherein the first mobile radio
2 terminal comprises a mobile communication device, and wherein the second
mobile radio terminal comprises a key permitting operation of the mobile
4 communication device only when the locations of the mobile communica-
tion device and the key are within the specified distance.

-21-

20. The method of claim 17, wherein the step of generating
2 a control signal based upon said comparison comprises the step of generat-
ing a control signal if the first mobile radio terminal is at a first specified
4 location and the second mobile radio terminal is at a second specified
location spacially separated from the first specified location.

21. The method of claim 17, wherein the comparing step
2 further comprises the step of comparing, at the location server, a current
time with a preselect time.

22. The method of claim 21, wherein the generating step
2 comprises the step of generating a control signal if the first mobile radio
terminal is at a first specified location, the second mobile terminal is at a
4 second specified location and the current time matches the preselect time.

-22-

23. A method of generating a control signal comprising the
2 steps of:

receiving, at a location server, an initiation signal from a first
4 mobile radio terminal;

transmitting, by the location server, a location query to the
6 first mobile radio terminal and a second mobile radio terminal;

reporting, by the first and second mobile radio terminals,
8 respective locations of the first and second mobile radio terminals in re-
sponse to the location query;

comparing, at the location server, the received locations of the
10 first and second mobile radio terminals; and

12 generating a control signal based upon said comparison.

24. The method of claim 23, wherein the step of generating
a control signal based upon said comparison comprises the step of trans-
mitting, by the location server, a control signal activating the first mobile
radio terminal for use if the locations of the first and second mobile radio
terminals are either within, or separated by, a specified distance.

25. The method of claim 24, wherein the first mobile radio
2 terminal comprises a mobile communication device, and wherein the second
mobile radio terminal comprises a key permitting operation of the mobile
4 communication device only when the locations of the mobile communica-
tion device and the key are within the specified distance.

-23-

26. The method of claim 23, wherein the step of generating
a control signal based upon said comparison comprises the step of generat-
ing a control signal if the first mobile radio terminal is at a first specified
location and the second mobile radio terminal is at a second specified
location spacially separated from the first specified location.

27. A method of generating a control signal comprising the
steps of:

monitoring, at a location server, locations of N mobile radio
terminals, wherein $N \geq 2$, said location server remote from the N mobile
radio terminals;

comparing, at the location server, the monitored locations of
the N mobile radio terminals; and

generating, at the location server, a control signal based upon
said comparison.

-24-

28. The method of claim 27, wherein

2 the step of comparing, at the location server, the monitored
locations of the N mobile radio terminals comprises the step of comparing
4 the monitored locations of the N mobile radio terminals with M different
specified locations, wherein $M \leq N$, and

6 the step of generating, at the location server, a control signal
based upon said comparison comprises the step of generating, at the loca-
8 tion server, a control signal if at least one of the N mobile radio terminals is
located at each of the M different specified locations.

29. The method of claim 27, wherein the comparing and
generating steps comprise the steps of:

2 comparing, at the location server, the monitored locations of
the N mobile radio terminals with N specified locations assigned to each of
4 the N mobile radio terminals; and


6 generating, at the location server in response to said compari-
son, the control signal if each of the N mobile radio terminals is located at
8 its assigned location.

30. The method of claim 29, wherein the N specified loca-
2 tions include N different specified locations.

-25-

ABSTRACT

5 A method of generating a control signal to enable or inhibit a
wide variety of applications is provided. The method generally includes the
steps of determining the location of a first mobile radio terminal, determin-
10 ing the location of a second mobile radio terminal, comparing the locations
of the terminals, and generating a control signal based upon the compari-
son. The control signal may be generated if the first and second mobile
radio terminals are within a specified distance of one another. Alterna-
tively, the control signal may be generated if the first and second mobile
radio terminals are separated by at least a specified distance from one
another. Additionally, the control signal may be generated if it is deter-
15 mined that the first mobile radio terminal is at a first specified location and
the second mobile radio terminal is at a second specified location spacially
separated from the first specified location. Further, the control signal may
be generated if the first and second mobile radio terminals are at specified
locations at a preselect time.



16.

2/8




FIG. 2

3/8




FIG 3

4/8




FIG. 4




FIG. 8

5/8





FIG. 5



7/8




FIG 7

8/8




FIG 9




FIG 10

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; that

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: Method of Generating Control Signals Based on Location of Radio Terminals the specification of which:

☒ is attached hereto. ☐ was filed on _____
as Application Serial No. _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment specifically referred to above, and that I believe the named inventor(s) to be the original and first inventor(s) of the subject matter which is claimed and for which a patent is sought, and hereby acknowledge the duty to disclose information which is material to the examination of the application in accordance with §1.56 (reprinted on the back) of Title 37 of the Code of Federal Regulations.

I also hereby state that no patent applications on this invention have previously been filed in countries foreign to the United States of America, except as follows:

COUNTRY	APPLICATION NUMBER	DATE FILED (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C. 119
			yes _____ no _____
			yes _____ no _____
			yes _____ no _____

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status: patented, pending, abandoned)
_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status: patented, pending, abandoned)

I hereby appoint Richard S. Phillips (Reg. No. 17,314), Wm. A. VanSanten (Reg. No. 22,810), Jeffrey L. Clark (Reg. No. 29,141), John S. Mortimer (Reg. No. 30,407), F. William McLaughlin (Reg. No. 32,273), and Dean A. Monco (Reg. No. 30,091), each registered to practice before the United States Patent and Trademark Office and practicing as the firm of **WOOD, PHILLIPS, VAN SANTEN, CLARK & MORTIMER, 500 WEST MADISON STREET, SUITE 3800, CHICAGO, ILLINOIS 60661 (Telephone 312-876-1800)**, and Donald D. Mondul (Reg. No. 29,957), Charles L. Moore, Jr. (Reg. No. 33,742), David G. Matthews (Reg. No. 33,959), Kevin A. Sembrat (Reg. No. 36,673), Debra K. Stephens (Reg. No. 38,211), James S. Finn (Reg. No. 38,450), David K. Purks (Reg. No. 40,133), Mark C. Terrano (Reg. No. 40,200), Stephen A. Calogero (Reg. No. 41,491), Kermit D. Lopez (Reg. No. 41,953), and Herbert V. Kerner (Reg. No. 42,721), my attorneys with full power of substitution and revocation, to prosecute this application, to make alterations or amendments therein, to receive the patent and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the firm. All telephone inquiries may be directed to:

Dean A. Monco

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of sole or first Joint Inventor David R. Irvin Citizenship United States

Inventor's Signature David R. Irvin Date 7 April 99

Residence 1546 Iredell Drive, Raleigh, NC 27608

Post Office Address c/o Ericsson Inc., 7001 Development Drive, Research Triangle Park, NC 27709

Full name of second Joint Inventor, if any Ali S. Khayrallah Citizenship Lebanon

Inventor's Signature _____ Date _____

Residence 113 Streamview Drive, Apex, NC 27502

Post Office Address c/o Ericsson Inc., 7001 Development Drive, Research Triangle Park, NC 27709

Full name of third Joint Inventor, if any _____ Citizenship _____

Inventor's Signature _____ Date _____

Residence _____

Post Office Address _____

Full name of fourth Joint Inventor, if any _____ Citizenship _____

Inventor's Signature _____ Date _____

Residence _____

Post Office Address _____

Full name of fifth Joint Inventor, if any _____ Citizenship _____

Inventor's Signature _____ Date _____

Residence _____

Post Office Address _____

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; that

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: Method of Generating Control Signals Based on Location of Radio Terminals the specification of which:

☒ is attached hereto. ☐ was filed on _____
as Application Serial No. _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment specifically referred to above, and that I believe the named inventor(s) to be the original and first inventor(s) of the subject matter which is claimed and for which a patent is sought, and hereby acknowledge the duty to disclose information which is material to the examination of the application in accordance with §1.56 (reprinted on the back) of Title 37 of the Code of Federal Regulations.

I also hereby state that no patent applications on this invention have previously been filed in countries foreign to the United States of America, except as follows:

COUNTRY	APPLICATION NUMBER	DATE FILED (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C. 119
			yes _____ no _____
			yes _____ no _____
			yes _____ no _____

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status: patented, pending, abandoned)
_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status: patented, pending, abandoned)

I hereby appoint Richard S. Phillips (Reg. No. 17,314), Wm. A. VanSanten (Reg. No. 22,810), Jeffrey L. Clark (Reg. No. 29,141), John S. Mortimer (Reg. No. 30,407), F. William McLaughlin (Reg. No. 32,273), and Dean A. Monco (Reg. No. 30,091), each registered to practice before the United States Patent and Trademark Office and practicing as the firm of **WOOD, PHILLIPS, VAN SANTEN, CLARK & MORTIMER, 500 WEST MADISON STREET, SUITE 3800, CHICAGO, ILLINOIS 60661 (Telephone 312-876-1800)**, and Donald D. Mondul (Reg. No. 29,957), Charles L. Moore, Jr. (Reg. No. 33,742), David G. Matthews (Reg. No. 33,959), Kevin A. Sembrat (Reg. No. 36,673), Debra K. Stephens (Reg. No. 38,211), James S. Finn (Reg. No. 38,450), David K. Purks (Reg. No. 40,133), Mark C. Terrano (Reg. No. 40,200), Stephen A. Calogero (Reg. No. 41,491), Kermit D. Lopez (Reg. No. 41,953), and Herbert V. Kerner (Reg. No. 42,721), my attorneys with full power of substitution and revocation, to prosecute this application, to make alterations or amendments therein, to receive the patent and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the firm. All telephone inquiries may be directed to:

Dean A. Monco

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of sole or first Joint Inventor David R. Irvin Citizenship United States

Inventor's Signature _____ Date _____

Residence 1546 Iredell Drive, Raleigh, NC 27608

Post Office Address c/o Ericsson Inc., 7001 Development Drive, Research Triangle Park, NC 27709

Full name of second Joint Inventor, if any Ali S. Khayrallah Citizenship Lebanon

Inventor's Signature Ali S. Khayrallah Date 3/31/99

Residence 113 Streamview Drive, Apex, NC 27502

Post Office Address c/o Ericsson Inc., 7001 Development Drive, Research Triangle Park, NC 27709

Full name of third Joint Inventor, if any _____ Citizenship _____

Inventor's Signature _____ Date _____

Residence _____

Post Office Address _____

Full name of fourth Joint Inventor, if any _____ Citizenship _____

Inventor's Signature _____ Date _____

Residence _____

Post Office Address _____

Full name of fifth Joint Inventor, if any _____ Citizenship _____

Inventor's Signature _____ Date _____

Residence _____

Post Office Address _____